

LED Display Panel

A Brand New Way to display products !!



FEATURES OF DRACO LED POSTER

- 1. Attractive HD Visual Display**
2.5mm LED pixel pitch, high refresh rate (>3.6kHz) and brightness (>1000cd/m²) together give a spectacular visual effect. The vivid real color of content is faithfully displayed.
- 2. Multiple Panel Display**
Endless combinations of display are possible. The panels can be joined together to form various sizes and shapes for one big screen or several panels synchronized to display identical materials. It is all up to designers' creativities.
- 3. Highly Portable and Simple Installation**
The Draco LED Poster is just 38mm thick and weights 35kg. It makes transportation and installation so easy. Stands and mounting brackets allow the panel to standup, wall hung vertically or horizontally.
- 4. Powerful Scheduler**
Our control software helps to schedule the contents, manage the synchronization of multi-panel to meet different needs.



SPECIFICATIONS SHEET

Parameter	Value
Physical Parameter	
Pixel Configuration	3in1 SMD
Pixel Pitch (mm)	2.571
Module Dimensions (H×W×D)/(mm)	288×216×8
Frame Dimensions (H×W×D)/(mm)	1990×622×35
Display Dimension(H×W)(mm)	1944×576
Display Resolution(H×W)	756×224
Net weight (kg)	35
Electronic Parameter	
Color gray scale (Bit)	14bit
Gray Scale per color(level)	16384
Refresh Rate(Hz)	>3600HZ
Scanning Mode	1/28
AC Power Supply Frequency(Hz)	50/60
Communication Way	U-disk/Wi-Fi/Internet
Optical parameters	
Brightness(nits)	1000
Color Temperature(K)	7500
Color Contrast	2500
Optimal Horizontal Viewing Angle	160°
Optimal Vertical Viewing Angle	160°
Electrical Parameter	
AC Input Voltage(V)	100-240
AC Input Frequency(Hz)	50-60
Power Supply Factor	>0.9
AC Input Power Maximum Value(W)	600W±3%
AC Input Power Typical Value(W)	200W±3%
Circumstance Parameter	
Storage Temperature(°C)	-20~+60
Operating Temperature(°C)	-10~+40
Storage Humidity(RH)	10%~90%
Operating Humidity(RH)	10%~90%
Waterproof Rating	IP40/IP21
Lifetime Typical Value(hrs)	50000

